NATIONAL ADVISORY COMMITTEE
FOR AERONAUTICS

TECHNICAL NOTE

No. 1129

FLIGHT INVESTIGATION AT HIGH SPEEDS OF THE DRAG

OF THREE AIRFOILS AND A CIRCULAR CYLINDER

REPRESENTING FULL-SCALE PROPELLER SHANKS

By William H. Barlow

Langley Memorial Aeronautical Laboratory
Langley Field, Virginia

Washington
September 1946

NATIONAL ADVISORY COMMITTEE FOR AERONAUTICS

TECHNICAL NOTE NO. 1129

FLIGHT INVESTIGATION AT HIGH SPEEDS OF THE DRAG

OF THREE AIRFOILS AND A CIRCULAR CYLINDER

REPRESENTING FULL-SCALE PROPELLER SHANKS

By William H. Barlow

SUMMARY

Tests have been made at high speeds to determine
the drag of models, simulating propeller shanks, in the
form of a circular cylinder and three airfoils, the
NACA 16-025, the NACA 16-040, and the NACA 16-040 with
the rear 25 percent chord cut off. All the models had
a maximum thickness of $4\frac{1}{2}$ inches to conform with average
propeller-shank dimensions and a span of $20\frac{1}{4}$ inches.

For the tests the models were supported perpendicular
to the lower surface of the wing of an XP-51 airplane.
A wake-survey rake mounted below the wing directly
behind the models was used to determine profile drag
at Mach numbers of 0.3 to 0.8 over a small range of
angle of attack. The drag of the cylinder was also
determined from pressure-distribution and force measurements.

The results of the tests indicated that the drag of
the airfoils was lower than that of the cylinder over
the Mach number range investigated. The drag reduction
obtainable through the use of these airfoil sections in
place of a round shank increased with a decrease in air-
foil thickness ratio and reached maximum values at a
Mach number of 0.63 for the NACA 16-040 airfoils and 0.71
for the NACA 16-025 airfoil.

INTRODUCTION

During recent years the National Advisory Committee
for Aeronautics has conducted investigations for the
purpose of increasing the efficiency of propellers on

airplanes. One of the factors found to increase considerably the losses in propeller efficiency was the high drag of round shanks operating in high-velocity fields. Various methods for reducing shank drag were tried; among these methods was the use of cuffs or propeller shank fairings. Flight-test data from cuffed propellers on streamline bodies are scarce, and the available data were not obtained in any systematic manner so that the relative value of the cuffs tested could not be ascertained. Wind-tunnel tests of thick airfoil sections and cuffed propellers have not been obtained with proper scale, Mach number, and shank relief effects. Because of the scarcity of drag data on thick airfoils operating at high speeds, therefore, data for development and improvement of propeller shanks were considered desirable. A flight-test program was consequently begun at the Langley Laboratory of the NACA in order to determine full-scale relative drag characteristics of various shanks and shank fairings under conditions approaching those of propeller shanks on a streamline body operating at high forward speeds. A preliminary phase of this program consisted of tests of three thick airfoil models and a circular cylinder; these models were mounted perpendicular to the lower surface of the wing of an XP-51 airplane, which was operated at such speeds as to give local Mach numbers at the model station of from 0.30 to 0.80. At the model station the chordwise pressure gradients due to the wing simulated in some respects the gradients due to a propeller spinner. Tip relief conditions at a propeller shank arising from rapid spanwise decrease in blade thickness were approximated by using models of finite aspect ratio. The results of tests of the three thick airfoil models and the circular cylinder are given in the present paper. A comparison of the speed gains that might be realized by use of these thick airfoils in place of a round propeller shank is presented.

SYMBOLS

q dynamic pressure, pounds per square foot

p_0 free-stream static pressure, pounds per square foot

Δp local static pressure minus free-stream static pressure, pounds per square foot

d_O section profile drag of model, pounds per foot of span

d section pressure drag of model, pounds per foot of span

D drag of model, pounds

A frontal area, square feet

t model thickness, feet

c_{d_O} section profile-drag coefficient (d_O/qt)

c_d section pressure-drag coefficient (d/qt)

C_L airplane lift coefficient

M_O flight Mach number

M effective Mach number at model station

APPARATUS AND METHODS

The propeller-shank sections selected for the tests included a circular cylinder to represent a round shank and two symmetrical airfoils, the NACA 16-025 and the NACA 16-040. The 25-percent-thick airfoil represented a thin shank section and the 40-percent-thick airfoil, a thick shank section. The NACA 16-040 airfoil was also tested with the rear 25 percent chord cut off. A photograph of three of the models tested is presented as figure 1. Geometric characteristics of the models are given in figure 2. All models were of rectangular plan form and had a thickness of $4\frac{1}{2}$ inches to correspond to average shank dimensions. The models had a $20\frac{1}{4}$-inch span including the rounded tip, which was obtained by rotating the airfoil section 180° about the chord line. The aspect ratios of the models were 9.2, 2.1, 3.4, and 4.5 for the circular cylinder, the NACA 16-025, NACA 16-040, and modified NACA 16-040 airfoils, respectively, and were based on the assumption that the wing acted as a reflection plane. These values

of aspect ratio may be high because of a small gap between the model and the wing.

The models were mounted on a rod perpendicular to and extending from the lower surface of the left wing of an XP-51 airplane (fig. 3). The average clearance between the models and the wing surface was $\frac{3}{16}$ inch. (See fig. 4.) Provision was made to rotate the supporting rod in order to obtain a change in angle of attack from -6° to 6° for the airfoils and to rotate the cylinder through 200° for pressure-distribution measurements. The support rod was located at approximately 38 percent of the chord at the 40-percent-semispan station and was about 3 feet outboard of the propeller radius.

A wake-survey rake mounted 29 inches behind the support rod and 9 inches below the wing surface (figs. 4 and 5) provided data for determination of the profile-drag coefficient of the model center section. The distance of the rake behind the trailing edge of each model is shown in figure 5. Direct drag measurements on the cylinder were obtained by mounting the cylinder on a support rod equipped with electric strain gages. Pressure-drag data on the cylinder were obtained from pressure-distribution measurements made by means of two orifices 180° apart at each of six equally spaced span-wise stations (fig. 6). A complete survey at each station was obtained by rotating the cylinder 200° during a test run.

The local dynamic pressure q and the local Mach number M used in evaluating the data were determined from free-stream total pressure measured with the pitot tube mounted ahead of the airplane wing and from local static pressure measured with static-pressure tubes located on the right wing at the same chordwise and spanwise positions as those at which the models were located on the left wing. These pressure measurements were made simultaneously with measurements of the drag of the models. In the pressure-distribution tests of the cylinder the static-pressure measurements on the right wing were made with a rake of six static-pressure tubes, with each tube located at a distance below the wing surface corresponding to an orifice location in the cylinder (fig. 6). For the force tests of the cylinder and the wake surveys, the static pressure on

the right wing was measured with one static-pressure
tube located 9 inches below the wing surface (fig. 7),
which corresponds to station 3 in figure 6. The
difference between local Mach number at various distances
below the wing surface and free-stream Mach number is
presented in figure 6 for several flight Mach numbers.

In order to indicate the magnitude of the chordwise
variation of static pressure in the test region, the
chordwise pressure distributions, as determined from
measurements of static pressure on the lower surface
of the wing of another XP-51 airplane, are presented in
figure 9 for an airplane lift coefficient of about 0.15
and several flight Mach numbers. Static pressures
measured in the present tests at station 3 (9 in. below
the wing surface) are included in figure 9. Because of
the decrease in induced velocity with distance from the
wing surface, the chordwise gradients at station 3 may
be somewhat less than those indicated at the wing surface.

The angular position of the models with respect to
the airplane longitudinal axis was recorded by a mechanical
optical control-position recorder. The yaw angle of the
airplane was measured by means of a yaw vane mounted on
a boom 1 chord ahead of the right wing near the tip. The
angle of attack of the models was determined from the
angle of the model and of the airplane. Any difference
that might exist between the direction of flow over the
wing and the direction of flow in the free stream was
not taken into account. Air temperature used in the
determination of model Reynolds number was obtained by
means of a low-lag thermometer (fig. 7) connected to a
recording galvanometer. All instrumentation was standard
NACA equipment.

The tests were made at flight Mach numbers from 0.3
to 0.7 in 0.05 intervals. The corresponding range of
local Mach number at the test station was 0.3 to 0.8.
During each run the flight Mach number, the yaw angle,
and the normal acceleration were held constant.

RESULTS AND DISCUSSION

An indication of the extent to which the principal
flow conditions about a propeller shank were reproduced

in the present model tests may be obtained from an
examination of the variation of Mach number with distance
from the wing surface (fig. 8), the chordwise variation
of static pressure in the test region (fig. 9) and the
method used for simulating shank relief. The variation
of Mach number with distance from the wing surface
indicates that the Mach number decreased by about 0.03
in a distance of about 18 inches, whereas on an actual
propeller shank of equivalent length the Mach number
(based on the resultant of translational and rotational
velocities) would increase by about 0.1. The effect of
not reproducing the actual spanwise gradient is not
known. The negative chordwise pressure gradients over
the forward part of the test region followed by the
positive gradients over the rear part (fig. 9) are similar
to the gradients about a spinner on the nose of a typical
in-line engine installation. On a propeller the thinner
section adjacent to the shank may influence the flow over
the shank to some extent. In the present investigation
this condition was considered to be simulated, at least
approximately, by the use of models of finite aspect
ratio.

The variation with Mach number of the section drag
coefficient of the cylinder as determined from force-
test and pressure-distribution measurements is presented
in figure 10. The section pressure-drag coefficient
varied over the span of the cylinder, and for tests in
which the data are complete no consistent variation is
noted. An average minimum section pressure-drag coeffi-
cient of 0.5 is found between values of M of 0.425 and
0.475. With further increase in Mach number the section
pressure-drag coefficient increased rapidly to a value of
about 1.0 at a Mach number of 0.65 and then decreased at
still higher Mach numbers. The drag coefficient determined
from force tests appeared to be in reasonable agreement
with the pressure data.

The drag coefficients of the cylinder determined
from force tests, wake surveys, and pressure-distribution
tests are compared on the bases of Mach number and Reynolds
number in figures 11 and 12, respectively. In general,
results of the wake surveys are not in agreement with the
results of the force or pressure-distribution tests. Wake-
survey results indicated a lower minimum drag coefficient,
with drag coefficient increasing rapidly at a Mach number
of about 0.425 but increasing to a maximum value of about
1.5 at a value of M of 0.65. This maximum value of drag

coefficient is about 50 percent higher than the value
obtained by the force and pressure-distribution measure-
ments. No exact explanation for this discrepancy has
been ascertained; however, the oscillatory nature of
the wake, which is not accounted for in the momentum
equations used in reduction of wake-survey data, may be
the cause of this difference. Drag data for the airfoil
sections were obtained by the wake-survey method and
may therefore be subject to this same type of error.
Conditions in the wake of the airfoil at the survey
station, however, should approach more closely the con-
ditions assumed in the wake equations than the conditions
for the wake of the circular cylinder. If the surveys
had been made farther downstream of the models, the
effects of wake oscillations might have been reduced and
more conservative results obtained. Because of the
difficulty of supporting a rake in a more rearward
position, however, surveys could not be made farther
downstream.

The variation of section profile-drag coefficient
with angle of attack for several Mach numbers is presented
in figures 13, 14, and 15 for the NACA 16-025, the
NACA 16-040, and the modified NACA 16-040 airfoil models,
respectively. The variation of section profile-drag
coefficient with Mach number for zero angle of attack,
determined from the data in figures 13 to 15, is pre-
sented as figure 16. The section profile-drag coeffi-
cient had a minimum value of about 0.02 at Mach numbers
up to 0.63 for the NACA 16-025 airfoil model, a minimum
value of about 0.04 up to a Mach number of 0.50 for the
NACA 16-040 airfoil model, and a minimum value of 0.22
at a Mach number of 0.65 for the modified NACA 16-040
airfoil model. The large values of section profile-
drag coefficient, at low Mach numbers, for the modified
NACA 16-040 airfoil were probably associated with low
Reynolds numbers. The Mach number at which the section
profile-drag coefficient began to increase rapidly was
0.75 for the NACA 16-025 airfoil model and 0.60 for the
NACA 16-040 airfoil models. At Mach numbers greater
than 0.65 the section profile-drag coefficient of the
modified NACA 16-040 airfoil model was slightly higher
than the corresponding drag coefficient for the
NACA 16-040 airfoil model.

The variation of the drag of the cylinder and the
airfoil models with Mach number is presented in figure 17
as a plot of $D/p_0 A$ against Mach number. Over the range

of Mach number tested, the drag of the cylinder was higher than the drag of any of the airfoil models. The drag reduction obtained through use of the airfoils in place of a cylindrical shank increased with decrease in airfoil thickness ratio. A small reduction in drag at low Mach numbers and a large reduction in drag at high Mach numbers can be effected through use of the NACA 16-040 airfoil with the rear 25 percent chord cut off in place of the cylindrical shank. The maximum drag reduction was obtained at a Mach number of 0.63 for the NACA 16-040 airfoils and at a Mach number of 0.71 for the NACA 16-025 airfoil.

On the basis of the results of figure 17 an estimate was made of the increase in speed of a present-day fighter airplane operating at an altitude of 30,000 feet that may be obtained by fairing the exposed round shanks of a four-blade propeller by use of each of the three airfoil sections. The results are presented in figure 18 as the speed increase obtainable by a fairing of 1 inch on each round shank, although, of course, in the actual case more of the propeller shanks would have to be faired and the total increase in speed would therefore be greater than is shown in figure 18. These results are intended primarily to show the relative effectiveness of the various fairings. The maximum increase in speed obtainable by using the NACA 16-040 and the modified NACA 16-040 airfoil sections as fairings was estimated to be 4.0 to 4.5 miles per hour at a true airspeed of 430 miles per hour. The increase in speed obtainable by using the NACA 16-025 airfoil section was greater over the speed range considered than that obtainable by using the other two airfoil sections and had a maximum value of about 6 miles per hour at a true airspeed of 480 miles per hour.

CONCLUDING REMARKS

The results of tests of models simulating propeller shanks in the form of a cylinder and three airfoils - the NACA 16-025, the NACA 16-040 and a modified NACA 16-040, each having a maximum thickness equal to the cylinder diameter - indicated that the drag of the airfoils was lower than that of the cylinder over the Mach number range investigated (0.3 to 0.8). The drag reduction obtainable through the use of these airfoil sections in place of a

round shank increased with decrease in airfoil thickness
ratio and reached maximum values at a Mach number of 0.63
for the NACA 16-040 airfoils and 0.71 for the NACA 16-025
airfoil.

Langley Memorial Aeronautical Laboratory
    National Advisory Committee for Aeronautics
   Langley Field, Va., June 7, 1946

(a) Circular
cylinder.

(b) NACA 16-040
airfoil (modified).

(c) NACA 16-025
airfoil.

Figure 1.- Propeller-shank models.

Figure 2.- Geometric characteristics of propeller-shank models. Span of models, $20\frac{1}{4}$ inches, including rounded tip.

Fig. 2

Figure 3.- Wake-survey rake and support rod for propeller-shank models mounted on lower surface of wing of XP-51 airplane.

Fig. 3

(a) Front view.

(b) Side view.

Figure 4.- Circular cylinder mounted below lower surface
of wing of XP-51 airplane.

NACA 16-040 —   — NACA 16-025

Circular cylinder ——→

9"

— Survey rake

17$\frac{3}{4}$"

22$\frac{1}{2}$"

27$\frac{1}{2}$"

29"

NATIONAL ADVISORY
COMMITTEE FOR AERONAUTICS

Figure 5.- Location of models and wake-survey rake below lower
surface of wing of XP-51 airplane.

Fig. 5

Fig. 6   NACA TN No. 1129

Orifice station

1

2

3

4

5

6

6 spaces at 3 in.

18 in.

Figure 6.- Circular cylinder showing orifice stations.

Figure 7.- Static-pressure tube and thermometer
mounted below right wing of XP-51 airplane.

Figure 8.- Variation of increment of local Mach number above flight
Mach number with distance below right wing surface as determined
from static-pressure surveys.

Fig. 8

Fig. 9

Figure 9.- Typical chordwise pressure distributions at wing surface in test region at various flight Mach numbers. Pressure coefficients for station 3 ($C_L = 0.15$) also shown.

Figure 10.- Variation with Mach number of section drag coefficient for the circular cylinder.

Fig. 10

Fig. 11

Figure 11.- Variation with Mach number of section drag coefficient
of the circular cylinder.

Figure 12.- Variation with Reynolds number of section
drag coefficient of the circular cylinder.

Fig. 13

Figure 13.- Variation of section profile-drag coefficient (based on thickness) with angle of attack at various Mach numbers for the NACA 16-025 airfoil model.

NATIONAL ADVISORY
COMMITTEE FOR AERONAUTICS

Figure 14.- Variation of section profile-drag coefficient (based on thickness) with angle of attack at various Mach numbers for the NACA 16-040 airfoil model.

Fig. 14

Fig. 15

Figure 15.- Variation of section profile-drag coefficient (based on thickness) with angle of attack at various Mach numbers for the modified NACA 16-040 airfoil model.

Figure 16.- Variation of section profile-drag coefficient (based on thickness) with Mach number for the three airfoil models at zero angle of attack.

Fig. 17   NACA TN No. 1129

Figure 17.- Variation with Mach number of drag of the circular cylinder and the three airfoil models at zero angle of attack.

Figure 18.- Estimated increase in speed obtainable for a typical fighter airplane with a four-blade propeller by fairing 1 inch of each round shank to an airfoil section. Airplane operating at 30,000 feet.

Fig. 18